



47 kg/m<sup>2</sup>

Resin + Mineral fillers  
+ Coating

5 YEARS  
WARRANTY

Anti-slip coating,  
DIN 51097.

Coating with excellent  
resistance to hydrolysis.

High coating  
UV resistant.

SUPERIOR HARDNESS coating  
(<0.01 mm according to UNE EN  
14688; maximum allowed 0.1 mm).

Antibacterial treatment  
R<2 ISO 22196.

Special cuts available.  
It can be cut on site by  
diamond saw

Recessed, raised or on Quare  
feet installation. Consult  
installation manual.

Technical specifications are subject to change without notice. Dimensional tolerances +/-5mm.

(\*) Maximum recommended cut. For other cuts, please consult us.



		A (mm)									
		900	1000	1100	1200	1300	1400	1500	1600	1700	1800
800	C	450	500	550	600	650	700	750	800	850	900
	H	30	30	30	30	33	33	33	35	35	35
	X*	0	50	100	150	50	100	150	50	100	150
	Y*	0	0	0	0	0	0	0	0	0	0
900	C	450	500	550	600	650	700	750	800	850	900
	H	30	30	30	30	33	33	33	35	35	35
	X*	0	50	100	150	50	100	150	50	100	150
	Y*	100	100	100	100	100	100	100	100	100	100
1000	C	450	500	550	600	650	700	750	800	850	900
	H	30	30	30	30	33	33	33	35	35	35
	X*	0	50	100	150	50	100	150	50	100	150
	Y*	200	200	200	200	200	200	200	200	200	200

### COMPOSITION

A 900 - 1800 | B 800-1000



Class B / PN 18 / Class 2

### STANDARD COLOURS



### SPECIAL COLOURS



### RAL



### NCS



### WASTES

#### EXTRA FLAT SHOWER WASTE

Flow rate 35 l/mn  
Height 54 mm



#### VERTICAL SHOWER WASTE

Flow rate 35 l/mn  
Height 96 mm



#### HIGH FLOW SHOWER WASTE

Flow rate 50 l/mn  
Height 80 mm



#### SLIM + SHOWER WASTE

Flow rate 27 l/mn  
Height 56 mm



### WASTE COVER

RESIN WASTE COVER IN COMPOSITION  
FINISH (SLATE), COLOURED

