



QUAREX
Resin + Mineral fillers
+ Coating

5 YEARS GUARANTEE

Anti-slip coating.
DIN 51097.

Coating with excellent
resistance to hydrolysis.

High coating
UV resistant.

SUPERIOR HARDNESS coating
(<0.01 mm according to UNE EN 14688; maximum allowed 0.1 mm).

Antibacterial treatment
R<2 ISO 22196.

Special cuts available.
It can be cut on site by
diamond saw

Recessed, raised or on Quare
feet installation. Consult
installation manual.

Technical specifications are subject to change without notice. Dimensional tolerances +/-5mm.

45 kg/m²

(*) Maximum recommended cut. For other cuts, please consult us.



		A (mm)									
		900	1000	1100	1200	1300	1400	1500	1600	1700	1800
700	C	95	95	95	95	95	95	95	95	95	95
	H	25	25	25	25	25	25	25	25	25	25
	X*	0	50	100	150	50	100	150	50	100	150
	Y*	0	0	0	0	0	0	0	0	0	0
800	C	95	95	95	95	95	95	95	95	95	95
	H	25	25	25	25	25	25	25	25	25	25
	X*	0	50	100	150	50	100	150	50	100	150
	Y*	100	100	100	100	100	100	100	100	100	100
900	C	95	95	95	95	95	95	95	95	95	95
	H	25	25	25	25	25	25	25	25	25	25
	X*	0	50	100	150	50	100	150	50	100	150
	Y*	200	200	200	200	200	200	200	200	200	200

PIZARRA

A 900-1800 | B 700-900



Class C / PN24 / Class 3

STANDARD COLOURS



SPECIAL COLOURS



RAL



NCS



WASTES

EXTRA FLAT SHOWER WASTE

Flow rate 35 l/mn
Height 54 mm



VERTICAL SHOWER WASTE

Flow rate 35 l/mn
Height 96 mm



HIGH FLOW SHOWER WASTE

Flow rate 50 l/mn
Height 80 mm



SLIM + SHOWER WASTE

Flow rate 27 l/mn
Height 56 mm



WASTE COVER

SAME-COLOURED WASTE
IN RESIN WITH PIZARRA TEXTURE

