



Resin + Mineral fillers
+ Coating

5 YEARS
GUARANTEE

Anti-slip coating,
DIN 51097.

Coating with excellent
resistance to hydrolysis.

High coating
UV resistant.

SUPERIOR HARDNESS coating
(<0.01 mm according to UNE EN
14688; maximum allowed 0.1 mm).

Antibacterial treatment
R<2 ISO 22196.

Special cuts available.
It can be cut on site by
diamond saw

Recessed, raised or on Quare
feet installation. Consult
installation manual.

Technical specifications are subject to change without notice. Dimensional tolerances +/-5mm.

(*) Maximum recommended cut. For other cuts, please consult us.



PIZARRA
A 700-2100 | B 700-1100



Class C / PN24 / Class 3



LISO
A 700-2100 | B 700-1000



Class B / PN 18 / Class 2



COCODRILO
A 700-2100 | B 700-900



Class B / PN 18 / Class 2

B (mm)		A (mm)														
		700	800	900	1000	1100	1200	1300	1400	1500	1600	1700	1800	1900	2000	2100
700	C	455	455	455	455	465	465	460	460	460	650	650	650	650	650	650
	H	25	25	25	25	25	25	30	30	30	30	30	30	30	30	30
	X*	0	100	200	200	200	300	200	300	300	300	200	300	100	200	300
800	C	455	455	455	455	465	460	460	460	650	650	650	650	650	650	650
	H	25	25	25	25	25	30	30	30	30	30	30	30	30	30	30
	X*	0	100	200	200	200	300	200	300	300	300	200	300	100	200	300
900	C	450	450	450	500	490	490	465	465	465	650	650	650	650	650	650
	H	25	25	25	25	25	30	30	30	30	30	30	30	30	30	30
	X*	0	100	200	200	200	300	200	300	300	300	200	300	100	200	300
1000	C	500	500	500	500	490	490	465	465	465	650	650	650	650	650	650
	H	25	25	25	25	25	30	30	30	30	30	30	30	30	30	30
	X*	0	100	200	200	200	300	100	200	300	100	200	300	100	200	300
1100	C					460	460	460	460	460	650	650	650			
	H					25	25	25	30	30	30	30	30			
	X*					100	200	300	100	200	300	100	200	300		

B (mm)		A (mm)														
		700	800	900	1000	1100	1200	1300	1400	1500	1600	1700	1800	1900	2000	2100
700	C	455	455	455	455	455	455	465	465	465	650	650	650	650	650	650
	H	25	25	25	25	25	25	30	30	30	30	30	30	30	30	30
	X*	0	100	200	100	200	300	100	200	300	100	200	300	100	200	300
800	C	455	455	455	455	455	455	465	465	465	650	650	650	650	650	650
	H	25	25	25	25	25	25	30	30	30	30	30	30	30	30	30
	X*	0	100	200	100	200	300	100	200	300	100	200	300	100	200	300
900	C	455	455	455	455	455	455	465	465	465	650	650	650	650	650	650
	H	25	25	25	25	25	25	30	30	30	30	30	30	30	30	30
	X*	0	100	200	100	200	300	100	200	300	100	200	300	100	200	300
1000	C	455	455	455	455	455	455	465	465	465	650	650	650	650	650	650
	H	25	25	25	25	25	25	30	30	30	30	30	30	30	30	30
	X*	0	100	200	100	200	300	100	200	300	100	200	300	100	200	300

B (mm)		A (mm)														
		700	800	900	1000	1100	1200	1300	1400	1500	1600	1700	1800	1900	2000	2100
700	C	455	455	455	455	455	455	465	465	465	650	650	650	650	650	650
	H	25	25	25	25	25	25	30	30	30	30	30	30	30	30	30
	X*	0	100	200	100	200	300	100	200	300	100	200	300	100	200	300
800	C	455	455	455	455	455	455	465	465	465	650	650	650	650	650	650
	H	25	25	25	25	25	25	30	30	30	30	30	30	30	30	30
	X*	0	100	200	100	200	300	100	200	300	100	200	300	100	200	300
900	C	455	455	455	455	455	455	465	465	465	650	650	650	650	650	650
	H	25	25	25	25	25	25	30	30	30	30	30	30	30	30	30
	X*	0	100	200	100	200	300	100	200	300	100	200	300	100	200	300

STANDARD COLOURS

PURE WHITE

CREMA

GREY

GREGE

SILK GREY

FANGO

MACCHIATO

TERRA

GRAFITE

ANTRACITE

BLACK

NATURAL WHITE
Only available
in Pizarra texture

SPECIAL COLOURS

GOLD

FOSSIL

TERRACOTTA

RAL

213 RAL

NCS

1950 NCS

PRINT

OXIDE

RUST

CITY

CARRARA

ONIX

IRIS

Only available in Pizarra and Liso textures

WASTES

EXTRA FLAT SHOWER WASTE

Flow rate 35 l/mn
Height 54 mm

VERTICAL SHOWER WASTE

Flow rate 35 l/mn
Height 96 mm

HIGH FLOW SHOWER WASTE

Flow rate 50 l/mn
Height 80 mm

SLIM + SHOWER WASTE

Flow rate 27 l/mn
Height 56 mm

GRIDS

Stainless steel grid

Coloured stainless steel grid

Coloured grid, Pizarra texture

PVD

BLACK GLOSSY

TITANIUM GLOSSY

GOLD GLOSSY

COPPER GLOSSY

