

3.5" drain opening pre-drilled

9,2 lb/ft²

QUAREX Resin+Mineral fillers+Coating	5 YEARS GUARANTEE	Slip Resistant: Compliant with section 8.6 of ASTM F462 - 79 (R2007)	Resistant to hydrolysis	High Coating resistance.
SUPERIOR HARDNESS coating	Anti-bacterial treatment	Can be cut on site	ADA Compliant	Consult installation manual.

Shower bases are in compliance with the CSA B45.5-17 / IAPMO Z124-2017 standard. Mass Code Approved.



STREET
A 35 3/8" - 70 7/8"
B 27 1/2" - 39 3/8"

		A (inch)							
		35 3/8	36	40	42	48	60	66	70 7/8
27 1/2	C	6 1/4	6 1/4	6 1/4	6 1/4	6 1/4	6 1/4	6 1/4	6 1/4
	H	1 1/8	1 1/8	1 1/8	1 1/8	1 1/8	1 1/8	1 1/4	1 1/4
30	C	6 1/4	6 1/4	6 1/4	6 1/4	6 1/4	6 1/4	6 1/4	6 1/4
	H	1 1/8	1 1/8	1 1/8	1 1/8	1 1/8	1 1/8	1 1/4	1 1/4
32	C	6 1/4	6 1/4	6 1/4	6 1/4	6 1/4	6 1/4	6 1/4	6 1/4
	H	1 1/8	1 1/8	1 1/8	1 1/8	1 1/8	1 1/8	1 1/4	1 1/4
36	C	6 1/4	6 1/4	6 1/4	6 1/4	6 1/4	6 1/4	6 1/4	6 1/4
	H	1 1/8	1 1/8	1 1/8	1 1/8	1 1/8	1 1/8	1 1/4	1 1/4
39 3/8	C	6 1/4	6 1/4	6 1/4	6 1/4	6 1/4	6 1/4	6 1/4	6 1/4
	H	1 1/8	1 1/8	1 1/8	1 1/8	1 1/8	1 1/8	1 1/4	1 1/4

Technical specifications are subject to change without notice. Dimensional tolerances +/- 3/16"

STANDARD COLORS



SPECIAL COLORS



RAL




NCS



DRAIN COVER ORION

RESIN DRAIN COVER INCLUDED, IN THE SAME COLOR AS THE SHOWER BASE



3 7/8" ≤ A ≤ 82 3/4"

Available in both textures.

Available in all colours.

Essential to confirm thickness: 1", 1 3/8" or 1 3/2".